

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

19



Europäisches Patentamt
European Patent Office
Offic européen des brevets

11 Publication number:

0 281 212
A1

12

EUROPEAN PATENT APPLICATION

21 Application number: 88200413.8

51 Int. Cl.4: A61B 17/36

22 Date of filing: 04.03.88

30 Priority: 05.03.87 NL 8700532

43 Date of publication of application:
07.09.88 Bulletin 88/36

84 Designated Contracting States:
AT BE DE ES FR GB IT LU NL


71 Applicant: Swart, Wilhelmus Johannes
Bernardus
A. van Gelderweg 1
NL-5361 CT Grave(NL)

72 Inventor: Swart, Wilhelmus Johannes
Bernardus
A. van Gelderweg 1
NL-5361 CT Grave(NL)

24 Representative: Baarslag, Aldert D. et al
Nederlandsch Octrooibureau Johan de
Wittlaan 15 P.O. Box 29720
NL-2502 LS Den Haag(NL)

54 Method and device for carrying out a therapeutic treatment by means of a refrigerant.

57 Method and device for e.g. the removal of warts by local freezing with a liquid refrigerant applied upon the wart area by means of a hollow rod (9) of which one end (8) is connected to the pressure-reducing valve (3) of a container (1) which contains a refrigerant under the pressure of its own gas phase, such as dimethylether, whilst at the other end (10) of the hollow rod (9) a cotton wool bud (11) is present which is placed upon the wart area after having received a dosis of dimethylether thereby cooling the bud to e.g. - 50°C.



EP 0 281 212 A1

Method and device for carrying out a therapeutic treatment by means of a refrigerant

The invention relates to a method for carrying out a therapeutic treatment, such as the removal of warts, on a part of the human or animal body by local freezing, the place to be treated being treated by means of a cotton wool bud or similar plug of absorbent material which has been cooled by means of a liquid refrigerant, which is present as liquid in the pressurised container and vaporises in escaping, at a
 5 temperature of less than 0°C.

Such a method is known and, to be specific, by making use clinically of liquid nitrogen which has a boiling point of -180°C. The cotton bud is immersed in the liquid nitrogen and then brought into contact with the place to be treated.

This, as it were, classical use of liquid nitrogen is subject to a number of practical drawbacks under
 10 clinical conditions. The availability and shelflife of liquid nitrogen is subject to limitations. The liquid nitrogen is made available in special double-walled, thermally insulated containers which are usually available only for a short time, usually only one day, for the treatment of warts. The general practitioner therefore has to arrange a special surgery.

For the effective removal of undesirable tissues, such as warts, it is necessary to destroy the cell
 15 structure by freezing within a very short period of time and, in view of its very low boiling point under atmospheric conditions, liquid nitrogen is in fact particularly suitable for this purpose.

The object of the invention is therefore to provide a method and device which offers a number of advantages over the known method and lacks the draw-backs associated therewith.

According to the invention, this object is achieved in the general sense, in that the cotton wool bud is
 20 provided on the end of a hollow rod which, with the insertion of a pressure-reducing and/or regulable shutoff valve, is connected to a sealed container which contains the refrigerant under the pressure of its own gas phase.

According to the invention, the refrigerant used is preferably a medium which is liquid even with a very low excess pressure and which is therefore kept in the liquid phase by its own gas phase without special
 25 cooling facilities, i.e. the major part of the volume of the reservoir contains liquid and a small quantity of gas, the liquid phase reducing to the extent that use occurs and the volume released being filled up by the gas phase. The outward flow takes place via the cotton wool bud on operating the valve. In this manner, the effect is obtained that refrigerants which have a boiling point is lower than 0°C rapidly bring about cell freezing as a result of further pressure reduction in the cotton wool bud and as a result of the large internal
 30 surface of the cotton wool bud which cause a lower temperature, (measured at the cotton wool bud) than the boiling point of the refrigerant and are amply sufficient to bring about cell freezing in a short time.

Consideration must be given here to refrigerants which boil at a temperature situated between 0°C and -50°C. In particular, these are refrigerants which boil between -0.5°C and -43°C. As an example of a refrigerant with a boiling point of -0.5°C, mention may be made of n-butane; as an example of a refrigerant
 35 having a boiling point of approximately -43°C, mention may be made of propane.

Suitable refrigerants might be halogenated hydrocarbons, such as tetrafluoromethane, trifluoromethane, monochlorotrifluoromethane, hexafluoroethane, monobromotrifluoromethane, monochlorodifluoromethane, monochloropentafluoroethane, dichlorodifluoromethane, 1,2-dichloro-, 1,1,2,2-tetrafluoroethane, trichloromonofluoromethane, 1,1,2-trichloro-, 1,2,2-trifluoroethane and 1,1-difluoroethane, propane, n-butane, and
 40 isobutane. These are, however, often environmentally harmful. Dimethyl ether is to be preferred since it is environmentally acceptable.

The pressure of the gas phase is preferably kept below 5 bar, preferably even little more than atmospheric pressure.

With the method according to the invention it is therefore possible in a very simple manner and in a
 45 manner which can be immediately available to immediately generate very low temperatures which are considerably below the boiling point of the particular refrigerant itself.

The device for using the method can be implemented in various manners.

According to the invention, said device preferably consists of a spray can for accommodating the refrigerant, a pressure-reducing and shut-off valve to be operated with a finger on an end wall of the spray
 50 can with a supply tube extending into the liquid phase and a discharge tube, connecting to the discharge opening of the valve, on the end of which the cotton wool bud is situated. Spray cans are easily kept in stock without special facilities being necessary so that the practitioner can use the treatment at any instant and is no longer dependent on the delivery of a container filled with liquid nitrogen. This means an important reduction in costs and, consequently, also that the treatment can be carried out more easily and more cheaply.

Attention is drawn to the fact that spray cans containing a refrigerant are known per se, for example for use in electronics. Spray cans which deliver a jet of refrigerant are, however, less suitable for medical treatments since the jet is difficult to aim satisfactorily and the refrigerant splutters in all directions at the place to be treated, as a result of which unintended effects are obtained.

5 Preferably, the valve has a low flow rate capacity of not more than 60 ml/minute, preferably 30 ml/minute, so that when the knob of the valve is pressed in, a measured quantity of refrigerant can easily be released.

Attention is drawn to the fact that it is known from the laid-open Dutch Patent Application 7,308,008 that use is made of a liquid refrigerant with a low boiling point for carrying out cryosurgical treatments such as the removal of an eye lens affected by cataract in cataract operations making use of adhesion to the rod-shaped object which is brought to a low temperature by means of the refrigerant and which is brought into contact with the place to be treated, such as the eye lens. In this device, which is known per se and of small construction and which may be regarded as a throwaway article, the liquid refrigerant is also present in a container and flows out via a cotton wool plug on operating a valve. Said plug acts, however, as a means for the absorption of coolant liquid and not for the treatment. The refrigerant is used for cooling a rod 15 which conducts heat rapidly and it is this rod which is used after cooling for carrying out the treatment. Said rod is situated at the end of the device facing away from the plug.

Furthermore, it is known from German Offenlegungsschrift 3,340,991 that dimethyl ether is used as propellant but also as solvent in spray cans for spraying-in of drugs to treat disorders of the air passages in the human or animal mouth, nose and throat cavity. This does not involve the freezing of cells but the application of a drug.

The invention will now be explained in more detail with reference to the drawing and with reference to examples.

The drawing shows a spray can 1 with an end wall 2 in which a pressure-reducing shut-off valve, not shown, and which is concealed from the eye by a covering cap 3 and can be operated if the covering cap is removed in a known manner and as is usual for spray cans. The spray can 1 contains a liquid refrigerant 4, the level of which is indicated at 5 and above which the gas phase 6 is situated. The valve extends into the liquid phase 4 of the refrigerant by means of a hose of flexible tubing 7. The debouchment of the valve contains a tube 8 into which a thinner tube 9 or narrow pipe is inserted and secured, the outlet opening of which is surrounded by a cotton wool plug 11.

On operating the valve, a quantity of liquid refrigerant flows via hose 7 and the valve through the tubes 8, 9 into the cotton wool plug 11, distributes itself there immediately over the large surface of the plug, vaporises and cools said cotton wool plug 11 to a very low temperature.

35

Examples:

Mention is made below of a number of refrigerants, the latter being followed by their normal boiling point and the latter by the lowest temperature which it was possible to measure after 30 seconds at the cotton wool bud as a result of activating the expanding refrigerant.

Refrigerant	Boiling point	Effective treatment temperature
dimethyl ether	-24.8°C	-45°C
45 difluorodichloro-		
methane	-29.8°C	-48°C
n-butane	-0.5°C	-29°C
isobutane	-11.7°C	-35°C
55 propane	-42.1°C	-50°C

Claims

1. Method for carrying out a therapeutic treatment, such as the removal of warts, on a part of the human or animal body by local freezing, the place to be treated being treated by means of a cotton wool bud which has been cooled by means of a liquid refrigerant which vaporises at a temperature of less than 0°C, characterized in that the cotton wool bud is provided at the end of a hollow rod which, with the insertion of a pressure-reducing valve and/or regulable shut-off valve, is connected to a sealed container which contains the refrigerant under the pressure of its own gas phase.


2. Method according to Claim 1, characterized in that a refrigerant is used which boils at a temperature situated between 0°C and -50°C, in particular between -0.5°C and -43°C.

3. Method according to Claim 1 or 2, characterized in that the pressure of the gas phase in the reservoir is kept below 5 bar.

4. Method according to Claim 1, 2 or 3, characterized in that dimethyl ether is used as refrigerant.

5. Device for carrying out the method according to one or more of the preceding Claims 1 to 4 incl., characterized in that said device consists of a spray can for accommodating the refrigerant, a pressure-reducing and shut-off valve to be operated with a finger on an end wall of the spray can with a supply tube extending into the liquid phase and a discharge tube connecting to the discharge opening of the valve, on the end of which the cotton wool bud is situated.

6. Device according to Claim 5, characterized in that the valve has a low flow rate capability of not more than 60 ml per minute, preferably 30 ml per minute.





European Patent
Office

PARTIAL EUROPEAN SEARCH REPORT
which under Rule 45 of the European Patent Convention
shall be considered, for the purposes of subsequent
proceedings, as the European search report

Application number

EP 88 20 0413

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
Y	US-A-3 220 414 (JOHNSTON) * Whole document *	5	A 61 B 17/36
	--		
Y	US-A-3 938 898 (REITKNECHT) * Figures; column 3, lines 26-34 *	5	
	--		
A	GBA-1 105 590 (PIGOT & SMITH) * Page 1, line 51 - page 2, line 8; page 2, lines 47-52; figures *	5	
	--		
A	GB-A-1 415 914 (FARBWERKE HOECHST)		
A	US-A-4 082 096 (BENSON)		
A	DE-A-3 340 991 (WOLFF)		
A	LU-A-67 705 (FRIGITRONICS)		
A	GB-A-1 163 573 (SWALLOWFIELD) -----		
			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			A 61 B A 61 F B 65 D
INCOMPLETE SEARCH			
<p>The Search Division considers that the present European patent application does not comply with the provisions of the European Patent Convention to such an extent that it is not possible to carry out a meaningful search into the state of the art on the basis of some of the claims.</p> <p>Claims searched completely: 5, 6 Claims searched incompletely: Claims not searched: 1-4 Reason for the limitation of the search:</p> <p>Method for treatment of the human or animal body by surgery or therapy (See art. 52(4) of the European Patent Convention)</p>			
Place of search The Hague		Date of completion of the search 07-06-1988	Examiner STEENBAKKER
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technical background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	